

Asus Intel-PC.



TA-D2

Sturdy and Considerate Design for Longer Component Lifespan

The TA-D2 is built to be sturdy, and comprised with high performance cooling for longer component lifespan.

[Add To Compare List](#)

Overview

Specifications

Download

Specifications

Dimension w/Bezel (W x H x D)	190 (W) x 434 (H) x 476 (D) mm
Case Size	ATX Mid Tower
MB Form Factor	ATX; microATX
Drive Bays	4 x Ext x 5.25" Bay 1 x Ext x 3.5" Bay 6 x Int x 3.5" Bay
System Fan (mm) Support	Front: 120 mm x 1 Rear: 120/92/80 mm x 1 Side venting hole with air duct
Expansion Slots	7
Weight	N.W. 5.5 kg G.W. 6.4 kg
Color Options (Front/Band /Side)	Black/Black/Black
Front I/O Configuration	USB x 2 + Audio x 2 USB x 2 + Audio x 2 + 1394 x 1

	ASUS E5200	ASUS E7400	ASUS E8400
Modelo	Asus Entry-863	Asus Super-Case SLIM	Asus Entry-863
Formato	ASUS Vento-863	Slim SCase	ASUS TA-D21
Fuente de alimentación	450-Watt CE	450-Watt CE	450-Watt CE
Hot Swap	-	-	-
Refrigeración	1*90 mm.	1*80 mm.	1*90 mm.
Refrigeración Adicional	Opcional	-	Opcional
Mainboard FSB	FSB: 1600 MHz.	FSB: 1600 MHz.	FSB: 1600 MHz.
Procesador	Intel E5200	Intel E7400	Intel E8400
FSB	800 MHz.	1,066 MHz.	1,333 MHz.
Caché L2	2 MB-L2	3 MB-L2	6 MB-L2
Frecuencia	2,50 GHz.	2,66 GHz.	3,00 GHz.
Virtualización Intel	-	-	-
Intel Speed-Step	-	-	-
Intel® Trusted Execution	-	-	-
Control Memory	-	-	-
Intel® Hiper-Threading	-	-	-
Intel® Turbo-Boost	-	-	-
Memoria RAM	2 GB (1 * 2GB) (Max:4GB)	2 GB (1 * 2GB) (Max:4GB)	4 GB (2 * 2GB) (Max:4GB)
Tipo RAM	DDR-2	DDR-2	DDR-2
Frecuencia RAM	800 MHz.	800 MHz.	800 MHz.
Controladora SATA	4 SATA de 3 GB/s + 1 UDMA	4 SATA de 3 GB/s + 1 UDMA	4 SATA de 3 GB/s + 1 UDMA
Niveles de RAID SATA	-	-	-
Controladora SAS	Opcional	Opcional	Opcional
Niveles de RAID SAS	-	-	-
Discos Instalados	1 * HDD 160 GB/SATA-2 - 8MB	1 * HDD 250 GB/SATA-2 - 8MB	1 * HDD 500 GB/SATA-2 - 8MB
LAN	1 Gbit. Ethernet + 10 USB	1 Gbit. Ethernet + 10 USB	1 Gbit. Ethernet + 10 USB
Controlador gráfico	Shared / 256 MB.	Shared / 256 MB.	Shared / 256 MB.
Unidades ópticas	DVD RW	DVD RW	DVD RW
Diskettera	Opcional	Opcional	Opcional
Disco Externo Backup	Opcional	Opcional	Opcional
Teclado	Sí	Sí	Sí
Ratón	Sí	Sí	Sí
Garantía standard	2 Años en Laboratorio	2 Años en Laboratorio	2 Años en Laboratorio
Tiempo de respuesta	RMA: 48 Horas	RMA: 48 Horas	RMA: 48 Horas
Certificados de calidad	ISO-9001 / ISO-14000	ISO-9001 / ISO-14000	ISO-9001 / ISO-14000
Precio Distribución (€).	246	325	385


VW202SR
 VW202SR - Optimize the Wide-format
 Visual Performance

High Contrast Ratio of 3000:1 for Sharper and Brighter Image Quality

[Add To Compare List](#)
Precio distribución: 98,50 €.

Overview

Specifications

Download

Specifications

TFT-LCD Panel	Panel Size: 20" Wide Screen True Resolution: WSXGA+ 1680x1050 Pixel Pitch: 0.258mm Brightness(Max): 300 cd/m ² Contrast Ratio (Max.): 3000 :1 (ASCR) Display Color: 16.7M Viewing Angle (CR≥ 10): 160°(H)/160°(V) Response Time: 5 ms
Video Features	SPLENDID Video Intelligence Technology SPLENDID Video Preset Modes (5 modes) Skin-Tone Selection (3 mode) Color Temperature Selection(5 modes)
Audio Features	Stereo Speakers 1Wx2 stereo RMS
Convenient Hotkey	SPLENDID Video Preset Mode Selection Auto. Adjustment Brightness Adjustment Volume Adjustment
Input / Output	PC Input: D-Sub PC Audio Input: 3.5mm Mini-jack
Signal Frequency	Analog Signal Frequency: 31.3-80.2KHz(H)/56-75Hz(V)
Power Consumption	Power Consumption < 49 W Power Saving Mode < 2 W
Mechanical Design	Chassis Colors: Black Tilt: +20°~-5° VESA Wall Mounting: 100x100mm
Security	Kensington lock
Dimension (WxHxD mm)	Phys.Dimension(WxHxD): 473x392x210mm Box Dimension(WxHxD): 570x455x150mm
Weight	Net Weight (Esti.): 4.4 kg Gross Weight (Esti.): 6.5 kg
Accessory	VGA cable Audio cable Power cord Quick start guide warranty card
Regulation Approval	Energy Star®, TCO03, CSA, CB, CE, FCC, CCC, BSMI, Gost-R, C-Tick, VCCI, PSB, RoHS, WEEE, WHQL 