



SPEC® CINT2006 Result

Copyright 2006-2008 Standard Performance Evaluation Corporation

ASUSTeK Computer Inc.

SPECint®2006 = 30.8

Asus P6T Deluxe (Intel Core i7-940)

SPECint_base2006 = 27.8

CPU2006 license: 13


Test sponsor: Intel Corporation

Tested by: Intel Corporation

Test date: Oct-2008

Hardware Availability: Nov-2008

Software Availability: Nov-2008



Hardware

CPU Name: Intel Core i7-940
 CPU Characteristics: Intel Turbo Boost Technology up to 3.20 GHz
 CPU MHz: 2933
 FPU: Integrated
 CPU(s) enabled: 4 cores, 1 chip, 4 cores/chip, 2 threads/core
 CPU(s) orderable: 1 chip
 Primary Cache: 32 KB I + 32 KB D on chip per core
 Secondary Cache: 256 KB I+D on chip per core
 L3 Cache: 8 MB I+D on chip per chip
 Other Cache: None
 Memory: 12 GB (6 x 2GB Samsung M378B5673DZ1-CF8 DDR3-1066 CL7)
 Disk Subsystem: 80 GB Intel X-25M SATA Solid-State Drive
 Other Hardware: None

Software

Operating System: Windows Vista Ultimate w/ SP1 (64-bit)
 Compiler: Intel C++ Compiler Professional 11.0 for IA32
 Build 20080930 Package ID: w_cproc_p_11.0.054
 Microsoft Visual Studio 2008 (for libraries)
 Auto Parallel: Yes
 File System: NTFS
 System State: Default
 Base Pointers: 32-bit
 Peak Pointers: 32-bit
 Other Software: None
 SmartHeap Library Version 8.1 from <http://www.microquill.com/>



SPEC CINT2006 Result

Copyright 2006-2008 Standard Performance Evaluation Corporation

ASUSTeK Computer Inc.

SPECint2006 = 30.8

Asus P6T Deluxe (Intel Core i7-940)

SPECint_base2006 = 27.8

CPU2006 license: 13

Test sponsor: Intel Corporation

Tested by: Intel Corporation

Test date: Oct-2008

Hardware Availability: Nov-2008

Software Availability: Nov-2008

Results Table

Benchmark	Base						Peak					
	Seconds	Ratio	Seconds	Ratio	Seconds	Ratio	Seconds	Ratio	Seconds	Ratio	Seconds	Ratio
400.perlbench	465	21.0	465	21.0	465	21.0	<u>333</u>	<u>29.4</u>	333	29.4	332	29.4
401.bzip2	578	16.7	578	16.7	578	16.7	<u>569</u>	<u>17.0</u>	568	17.0	569	17.0
403.gcc	337	23.9	337	23.9	337	23.9	<u>295</u>	<u>27.3</u>	292	27.6	301	26.8
429.mcf	210	43.4	207	44.0	208	43.9	<u>209</u>	<u>43.7</u>	209	43.6	209	43.7
445.gobmk	483	21.7	483	21.7	483	21.7	<u>431</u>	<u>24.3</u>	431	24.3	431	24.3
456.hmmmer	538	17.3	538	17.3	538	17.3	426	21.9	427	21.9	426	21.9
458.sjeng	538	22.5	538	22.5	538	22.5	514	23.5	514	23.5	514	23.5
462.libquantum	104	199	104	199	104	199	104	199	104	199	104	199
464.h264ref	653	33.9	652	33.9	652	33.9	<u>586</u>	<u>37.8</u>	586	37.8	587	37.7
471.omnetpp	278	22.5	278	22.5	278	22.5	<u>238</u>	<u>26.3</u>	237	26.3	238	26.3
473.astar	432	16.3	432	16.3	433	16.2	390	18.0	390	18.0	390	18.0
483.xalancbmk	252	27.3	253	27.3	253	27.3	252	27.3	253	27.3	253	27.3

Results appear in the order in which they were run. Bold underlined text indicates a median measurement.

General Notes

Tested systems can be used with Shin-G ATX case,
 PC Power and Cooling 1200W power supply
 System was configured with nVidia GTX 280 discrete graphics card
 Binaries were built on Windows Vista Ultimate (32-bit)
 OMP_NUM_THREADS set to number of logical processors as seen by the OS
 KMP_AFFINITY set to physical,0

Compiler Invocation

C benchmarks:
 icl -Qvc9 -Qc99

C++ benchmarks:
 icl -Qvc9

Portability Flags

403.gcc: -DSPEC_CPU_WIN32
 464.h264ref: -DSPEC_CPU_NO_INTTYPES -DWIN32
 483.xalancbmk: -Qoption,cpp,--no_wchar_t_keyword



SPEC CINT2006 Result

Copyright 2006-2008 Standard Performance Evaluation Corporation

ASUSTeK Computer Inc.

SPECint2006 = 30.8

Asus P6T Deluxe (Intel Core i7-940)

SPECint_base2006 = 27.8

CPU2006 license: 13

Test sponsor: Intel Corporation

Tested by: Intel Corporation

Test date: Oct-2008

Hardware Availability: Nov-2008

Software Availability: Nov-2008

Base Optimization Flags

C benchmarks:

-QxSSE4.2 -Qipo -O3 -Qprec-div- -Qopt-prefetch -Qparallel
-Qpar-runtime-control -Qvec-guard-write /F512000000

C++ benchmarks:

-QxSSE4.2 -Qipo -O3 -Qprec-div- -Qopt-prefetch -Qcxx-features
/F512000000 shlw32m.lib -link /FORCE:MULTIPLE

Peak Optimization Flags

C benchmarks:

400.perlbench: -QxSSE4.2(pass 2) -Qprof_gen(pass 1) -Qprof_use(pass 2)
-Qipo -O3 -Qprec-div- -Qansi-alias -Qopt-prefetch
/F512000000 shlw32m.lib -link /FORCE:MULTIPLE

401.bzip2: -QxSSE4.2(pass 2) -Qprof_gen(pass 1) -Qprof_use(pass 2)
-Qipo -O3 -Qprec-div- -Qopt-prefetch -Qansi-alias
/F512000000

403.gcc: -QxSSE4.2(pass 2) -Qprof_gen(pass 1) -Qprof_use(pass 2)
-Qipo -O3 -Qprec-div- /F512000000

429.mcf: -QxSSE4.2 -Qipo -O3 -Qprec-div- -Qopt-prefetch
/F512000000

445.gobmk: -QxSSE4.2(pass 2) -Qprof_gen(pass 1) -Qprof_use(pass 2)
-Qipo -O2 -Qprec-div- -Qansi-alias /F512000000

456.hmmer: -QxSSE4.2 -Qipo -O3 -Qprec-div- -Qunroll2 -Qansi-alias
/F512000000

458.sjeng: -QxSSE4.2(pass 2) -Qprof_gen(pass 1) -Qprof_use(pass 2)
-Qipo -O3 -Qprec-div- -Qunroll14 /F512000000

462.libquantum: basepeak = yes

464.h264ref: -QxSSE4.2(pass 2) -Qprof_gen(pass 1) -Qprof_use(pass 2)
-Qipo -O3 -Qprec-div- -Qunroll2 -Qansi-alias /F512000000

C++ benchmarks:

471.omnetpp: -QxSSE4.2(pass 2) -Qprof_gen(pass 1) -Qprof_use(pass 2)
-Qipo -O3 -Qprec-div- -Qansi-alias
-Qopt-ra-region-strategy=block /F512000000 shlw32m.lib
-link /FORCE:MULTIPLE

Continued on next page



SPEC CINT2006 Result

Copyright 2006-2008 Standard Performance Evaluation Corporation

ASUSTeK Computer Inc.

SPECint2006 = 30.8

Asus P6T Deluxe (Intel Core i7-940)

SPECint_base2006 = 27.8

CPU2006 license: 13

Test sponsor: Intel Corporation

Tested by: Intel Corporation

Test date: Oct-2008

Hardware Availability: Nov-2008

Software Availability: Nov-2008

Peak Optimization Flags (Continued)

```
473.astar: -QxSSE4.2(pass 2) -Qprof_gen(pass 1) -Qprof_use(pass 2)
          -Qipo -O3 -Qprec-div- -Qansi-alias
          -Qopt-ra-region-strategy=routine /F512000000 shlw32m.lib
          -link /FORCE:MULTIPLE
```

483.xalancbmk: basepeak = yes

Other Flags

C benchmarks:

403.gcc: -Dalloca=_alloca

The flags files that were used to format this result can be browsed at

<http://www.spec.org/cpu2006/flags/Intel-ic11.0-win32-revA.html>

<http://www.spec.org/cpu2006/flags/Intel-Win32-Platform.html>

You can also download the XML flags sources by saving the following links:

<http://www.spec.org/cpu2006/flags/Intel-ic11.0-win32-revA.xml>

<http://www.spec.org/cpu2006/flags/Intel-Win32-Platform.xml>

SPEC and SPECint are registered trademarks of the Standard Performance Evaluation Corporation. All other brand and product names appearing in this result are trademarks or registered trademarks of their respective holders.

For questions about this result, please contact the tester.
For other inquiries, please contact webmaster@spec.org.

Tested with SPEC CPU2006 v1.1.

Report generated on Tue Mar 3 14:05:47 2009 by SPEC CPU2006 PS/PDF formatter v6197.